

Chemical Guide

Info

Chemical Directions

Start Up

- #1 Fill Spa with Water
- #2 Place Mineral Purifier Cartridge in Filter Housing or in sock
- #3 Add 1-3 ounces of Scale Defense depending on Spa size
- #4 Add 16 ounces of Metal Protect (only when you drain and Fill Spa)
- #5 Add two ounces (4 Tablespoons) Oxidizer Shock
- #6 Two ounces Chlorine (dichlor) This activates the mineral cartridge
- #7 Test water with test strip
- #8 Balance ph up or down

Once per week

- #1 Add two ounces of Scale Defense
- #2 Add two ounces (4 Tablespoons) Oxidizer Shock
- #3 Add one Tbsp Chlorine granules (dichlor) per 100 gallons

After each use

- #1 Add 1 1/2 Tablespoons Oxidizer Shock per person
- #2 If water is cloudy add one additional Tbsp Chlorine granules

Change Mineral Purifier once every four months

Check your PH level weekly, it is very important to always maintain the proper PH level. You can use Muratic Acid to lower the PH.

If you have questions call 785-825-8888

All supplies may be ordered at www.aahsspas.com



410 N. MAIN, HILLSBORO, KS 67063

785.825.8888

spaguy4u@gmail.com

www.aahsspas.com